

NUOS PLUS WI-FI

HEAT PUMP WATER HEATER

HOT WATER | HEATING | RENEWABLES ariston.com

NUOS PLUS WI-FI FEATURES AND BENEFITS



200L Direct/250L Indirect

The renewable heat pump technology used by Nuos Plus Wi-Fi converts air into energy for domestic hot water, ensuring energy savings of up to 80% compared to traditional direct cylinders of the same capacity.

- / Under 4 hours heat up time, lowest on the market*
- / Highly efficient COP of 3.14**
- / Optional Wi-Fi control via Aqua Ariston Net app
- / "Plug & Play" no F-Gas qualifications needed to install
- / Extended operating temperature range (-10°C to 42°C)
- / R134a eco-friendly refrigerant gas for water temperatures up to 62°C in heat pump mode
- / Brand new working modes including daily/weekly programming and I-Memory
- / Full system integration with Ariston boilers through Sensys controls and BusBridgeNet technology**
- * Nuos Plus Wi-Fi 200D only
- ** Nuos Plus Wi-Fi





EFFICIENT



NET








CORROSION LEGIONELLA

ENERGY PATING



-MEMORY

I-Memory is a brand new mode which learns the user's water usage habits and automatically creates a pre-heating schedule. On week one, the unit is in a constant learning process, and during the second week, Nuos Plus Wi-Fi implements its findings to activate a completely tailored, intelligent heating schedule.





AQUA ARISTON NET



ARISTON NET

Nuos Plus Wi-Fi is fully compatible with the Aqua Ariston Net app. Connecting the Nuos to Ariston's dedicated smartphone app is completely optional, but provides ultimate control of a hot water system from the palm of your hand. From simply raising the temperature to setting a weekly hot water schedule, all tasks can be easily completed through the app, while in-depth energy consumption reports are provided to maximise savings. The Nuos Plus Wi-Fi 250i model can also be connected to the Ariston Net app when used in conjunction with an Ariston system boiler and Sensys HD Net Control.




NUOS PLUS WIFI HEAT PUMP WATER HEATER



PRODUCT DIMENSIONS

Legend

- A Inlet cold water 3/4" pipe
- **B** Outlet hot water 3/4" pipe
- C Condensate drainage connection
- **D** Auxiliary circuit 3/4" inlet pipe (250I)
- **E** Auxiliary circuit ¾" outlet pipe (250I)
- ${f F}$ Sheath for upper probe (S3) (250I)
- G Recirculation 3/4" pipe (250I)
- ${f H}$ Sheath for bottom probe (S2) (250I)
- I Display
- J Touch buttons



NUOS PLUS WI-FI Heating time (h:min) Nominal storage tank capacity (I) Sound power level (dB(A) Sound power level (silent mode) (dB(A) Max operating pressure (bar) Voltage/max power consumption (V/W) Max electrical power consumption in heat pump mode (W) **Ø150**mm 3208063 3208064 1.5m Tube 2m Tube Joint 45° Elbow 3208074 3208076 0.6m Flexible Pipe Duct Kit (Inlet/Outlet) Fixing Bracket (x2)

Furthermore, it reserves the right to change, without notice, the information of the products contained herein.

HOT WATER I HEATING I RENEWABLES

Customer Service: customer.service.uk@ariston.com | 0333 240 8777 Sales: salesoffice@ariston.com | 0333 240 6666

ariston.com















