

The Hoardfast system has a range of supports depending on your project requirement; from free-standing with mulliple stability options to floor-to-ceiling fix.

Some panels are only available with a **specific support option**, and panels can be cut on request.

Support Type	Specification		Panel	Panel Height
Equal (free-standing)		 Self supporting up to 2.7m high Support inserts into hollow flute of the panel Support protrudes each side of panel by 210mm* 	Standard uPVC	1.12m / 2.25m / 2.7m
Offset Weighted (free-standing)		 For additional stability up to 2.7m high Allows up to 3 x 16kg weights to be installed per support Support inserts into hollow flute of the panel Weights are secured with a bolt, washer and wingnut Support protrudes one side of panel by 600mm (construction side)* 	Standard uPVC	1.12m / 2.25m / 2.7m
Bolt Down (free-standing)		 For a more stable and permanent solution up to 2.7m high The support inserts into the hollow flute of the panel Support base plate secured to the floor with bolts 	Standard uPVC	1.12m / 2.25m / 2.7m

^{*}based on use with 35mm thick panel



Support Type	Specification		Panel	Panel Height
Universal (free-standing)		 For maximum stability Free-standing up to 3.1m high Standard: allows up to 3 x 16kg weights per support (Protrudes 645mm construction side) Long: will accommodate up to 6 x 16kg weights per support (Protrudes 900mm construction side) System secured at base using a hooked in u-channel and at the top using a hooked over pole 	Standard uPVC	2.25m / 2.7m / 3m
			Soundscreen	2.7m / 4m (can be cut for use between 2.25m - 3.1m)
			Firescreen	2.25m / 2.7m / 3.1m
			Flamescreen	2.25m / 2.7m
Floor-to-ceiling		 Floor-to-ceiling fixed solution up to 5m high Installed using supplied u-channels 	Standard uPVC	4m / 5m
			Soundscreen	2.7m / 4m
			Firescreen	3.5m / 4m / 4.5m
			Flamescreen	2.25m / 2.7m / 3.5m

This fact sheet is for illustrative purposes only and based on the latest information at the time of print. Installation methods may vary depending on specific project requirements. Westgate Global reserve the right to make changes at any time without notice.

J188-WSS-PFS-HF-SUP-080324 © Westgate Global Ltd

